

ALINCO



Repeater

VHF RS-D7

UHF RS-D8

The Cost-effective Digital Migration Solution.

- Professional design suitable for desktop, cabinet and rack installations.
- Outstanding Heat Dissipation with intelligent cooling fan.
- Analog / digital mixed mode detects signals automatically and sets correct mode.
- 9 LED indicators on the front panel display current status of operations.
- IP connection enables repeaters in different areas to communicate data, voice and packets over a TCP/IP based network.



Standard Accessories

- AC cord ADUA99
- Ethernet Cable ERW-20
- DC cable ADUA101



Specifications

General

Repeaters

Frequency Range	VHF 136~174MHz, UHF 400~470MHz
Channel Capacity / Zone Capacity	16
Channel Spacing	12.5KHz / 20KHz / 25KHz
Operating Voltage	DC13.8V±20% or AC 100-250V 50/60Hz
Dimension (approx. W x H x D)	482.5mm×338.5mm×132.5mm
Weight (approx.)	11.5kg

Transmitter

Repeaters

Frequency Stability	±0.5ppm
Power Output	VHF: 5 ~ 50W / UHF: 5 ~ 40W Adjustable by PC setting
Modulation Limiting	±2.5kHz@12.5kHz, ±4.0kHz@20kHz, ±5.0kHz@25kHz
FM Hum and Noise	-40dB@12.5kHz, -45dB@20/25kHz
Conducted/Radiated Emission	-36dBm@<1GHz, -30dBm@>1GHz
Adjacent Channel Power	-60dB@12.5kHz, -70dB@20/25kHz
4FSK Digital Modulation	12.5KHz(data only) : 7K60FXD / 12.5KHz(data+voice) : 7K60FXE
Analog Modulation	11K0F3E@12.5kHz, 14K0F3E @20kHz, 16K0F3E@25kHz
Digital Protocol / Vocoder	ETSI TS102361-1, -2, -3 / AMBE+2™

Receiver

Repeaters

Frequency Stability	±0.5ppm
Analog / Digital Sensitivity	0.3μV/(12dB SINAD) / 0.3μV/BER5%
Intermodulation	TIA603C : 75dB, ETSI : 60dB
Adjacent Channel Selectivity (ETSI)	65dB@12.5KHz/ 75dB@20/25KHz
Spurious Response Rejection	TIA603C:85dB ETSI:80dB
Hum and Noise	-40dB@12.5kHz, -45dB@20/25kHz
Audio Distortion	≤ 3% (typical)
Conducted Spurious Emission	-57dBm@<1GHz, -47dBm@>1GHz

Environmental Specifications

Operating Temperature	-30°C ~ +60°C
Storage Temperature	-45°C ~ +85°C
ESD	IEC 61000-4-2
Max Duty Cycle	100%

Alinco and ALINCO logo are registered trademarks of Alinco incorporated, Japan in United States, EU States, Russia, China and many other countries. Alinco can't be liable for pictorial or typographical inaccuracies. This product is not intended for sale in countries where FCC/CE conformity is essential for use and distributions. WINDOWS and AMBE trademarks are properties of their respective holders.

Authorized Dealer:

Copyright Alinco, Inc., Osaka, Japan. All rights reserved. Although Alinco has designed this brochure to be as accurate and comprehensive as possible, we reserve the right to make changes at any time to our equipment line, optional accessories, specifications, standard accessories, or availability of any such devices we manufacture and distribute. Please note that certain products and accessories may not be available in all countries of distribution therefore consult your Authorized Alinco Dealer for product availability and pricing. Colors of images herein may appear slightly different from actual products due to print.
 * Projections are not included in the declared dimension values.
 * Operator license may be required. Please consult your dealer for details.

ALINCO, INC. Electronics Division

Yodoyabashi Dai-Bldg 13F, 4-4-9 Koraibashi,
 Chuo-ku, Osaka 541-0043 Japan
 Phone: +81-6-7636-2362 Fax: +86-6-6208-3802
<http://www.ALINCO.com>
 E-mail: export@alinco.co.jp

FNFNENLNI-PE
 Ver.1.0.1 DMR-Re
 Printed in Japan



Please be sure to read the instruction manual before using the product for your safety.

